

Geometrie

	50	52	54	56	58	61
BB Drop	70mm	70mm	67mm	66.5mm	65mm	65mm
Crank Length	165mm	170mm	172.5mm	172.5mm	175mm	175mm
Dosah	372.2mm	380.8mm	387.8mm	396.9mm	405.9mm	412mm
Délka celé vidlice	400mm	400mm	400mm	400mm	400mm	400mm
Délka hlavové trubky	90mm	110mm	130mm	150mm	170mm	190mm
Délka horní trubky, horizontální	508mm	522mm	550mm	570mm	587mm	603mm
Délka sedlové trubky	440mm	460mm	480mm	500mm	520mm	540mm
Délka řetězové vzpěry	435.7mm	435.7mm	435.2mm	435.1mm	434.9mm	434.9mm
Handlebar Width	400mm	420mm	440mm	440mm	460mm	460mm
Rozvor	1021mm	1032mm	1037mm	1053mm	1064mm	1071mm
Saddle Width	143mm	143mm	143mm	143mm	143mm	143mm
Seatpost Length	350mm	400mm	400mm	400mm	400mm	400mm
Stack (Výška od vrcholu hlavové trubky po středové složení)	525mm	546mm	566mm	584mm	604mm	625mm
Stem Length	80mm	90mm	90mm	100mm	100mm	110mm
Stopa kola	77mm	74mm	67mm	67mm	64mm	61mm
Vyosení vidlice (offset)	50mm	50mm	50mm	50mm	50mm	50mm
Vzdálenost přední osa – středové složení	595mm	606mm	611mm	626mm	637mm	644mm
Výška rámu v rozkroku	736mm	750mm	772mm	791mm	812mm	832mm
Výška středového složení	289mm	289mm	292mm	292.5mm	294mm	294mm
Úhel hlavové trubky	70°	70.5°	71.5°	71.5°	72°	72.5°
Úhel sedlové trubky	75.5°	75.5°	74°	73.5°	73.3°	73°