

Geometrie

	46	49	52	54	56	58	61
BB Drop	71mm	71mm	71mm	69mm	69mm	67mm	67mm
Dosah	366mm	369mm	375mm	382mm	388mm	395mm	402mm
Délka celé vidlice	400mm	400mm	400mm	400mm	400mm	400mm	400mm
Délka hlavové trubky	100mm	115mm	125mm	140mm	155mm	170mm	190mm
Délka horní trubky, horizontální	501mm	509mm	534mm	550mm	563mm	578mm	597mm
Délka sedlové trubky	470mm	490mm	510mm	530mm	550mm	570mm	600mm
Délka řetězové vzpěry	425mm	425mm	425mm	425mm	425mm	425mm	425mm
Rozvor	1007mm	1007mm	1008mm	1020mm	1026mm	1034mm	1043mm
Stack (Výška od vrcholu hlavové trubky po středové složení)	523mm	540mm	554mm	566mm	582mm	597mm	618mm
Stopa kola	78mm	72mm	65mm	65mm	62mm	59mm	55mm
Vyosení vidlice (offset)	50mm	50mm	50mm	50mm	50mm	50mm	50mm
Vzdálenost přední osa – středové složení	592mm	592mm	593mm	605mm	611mm	618mm	627mm
Výška rámu v rozkroku	763.5mm	781.5mm	794.5mm	808.5mm	824.5mm	840.5mm	861.5mm
Výška středového složení	281.5mm	281.5mm	281.5mm	283.5mm	283.5mm	285.5mm	285.5mm
Úhel hlavové trubky	69.5°	70.5°	71.5°	71.5°	72°	72.5°	73°
Úhel sedlové trubky	75.5°	75.5°	74°	73.5°	73.25°	73°	72.5°